

5W-20 SYNTHETIC BLEND RACING MOTOR OIL

API SN, SN-RC and ILSAC GF-5

With CAM2 SuperPro Max Technology

Packaging: 55Gal (208L) drum

Part Number: 1G55W20R

PRODUCT DESCRIPTION

Powered by *CAM2 SuperPro MAX* technology this brand new premium quality motor oil is formulated from selected superior base oils and features advanced additive technology, providing the highest levels of equipment protection available. This oil is intended for use in passenger cars, light trucks, powerboats, motorcycles, and other stationary and mobile equipment.

SD OIL CO. 5W-20 SYNTHETIC BLEND RACING MOTOR OIL meets or exceeds the latest automotive manufacturers' requirements of API SN and SN-RC. This oil meets and exceeds ILSAC GF-5 requirements for use in passenger car, SUV and light duty truck gasoline engines. SD OIL CO. 5W-20 SYNTHETIC BLEND RACING MOTOR OIL shows improved high temperature deposit control, oil consumption and fuel economy.

SD OIL CO. 5W-20 SYNTHETIC BLEND RACING MOTOR OIL meets API Service Categories **API SN, SM, SL, SJ, SH, SG, SF** and **ILSAC GF-5, GF-4, GF-3, GF-2 & GF-1** on applicable viscosity grades. It has enhanced wear protection and outstanding resistance to thermal breakdown at operating temperatures.

FEATURES

SD OIL CO. 5W-20 SYNTHETIC BLEND RACING MOTOR OIL provides:

- Excellent Fuel Economy
- Excellent volatility for low oil consumption
- Excellent protection from deposits at all operating temperatures
- Excellent cold-cranking capabilities
- Excellent anti-wear, anti-foam, bearing corrosion and anti-rust protection
- Advanced varnish & sludge protection
- Superior Synthetic Blend Protection against thermal breakdown
- Meets or exceeds API Resource Conserving (RC) standards

BENEFITS

Compared to conventional oils:

- Excellent lubrication at extremely low temperatures
- Premium protection for extremely high temperatures
- Lower oil consumption under high speed conditions
- Protection against harmful deposits and acids, which aids in a clean running and lasting engine
- Reduced volatility, less top-up compared to conventional oils.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES SD OIL CO. SYNTHETIC BLEND MOTOR OIL

TEST	RESULTS
SAE Viscosity Grade	5W-20
API Gravity	32.78
Viscosity, cSt, 40°C	49.21
Viscosity, cSt, 100°C	8.59
Viscosity Index	153
Pour Point, °C	-48
API RC (Resource Conserving)	YES
ILSAC GF-5	YES
API Service	SN, SM, SL, SJ

* Follow the vehicle manufacturer's recommendation for the right viscosity grade and API Service Category.

